

UR16e technical details



Specifications

Payload	16 kg (35.3 lbs)
Reach	900 mm (35.4 in)
Degrees of freedom	6 rotating joints
Programming	12 inch touchscreen with polyscope graphical user interface

Performance

Power, Consumption, Maximum Average	585 W
Power, Consumption, Typical with moderate operating settings (approximate)	350 W

Safety	17 configurable safety functions
--------	----------------------------------

Certifications	EN ISO 13849-1, PLd Category 3, and EN ISO 10218-1
----------------	--

Force Sensing, Tool Flange Range	Force, x-y-z	Torque, x-y-z
	160.0 N	10.0 Nm
Precision	5.0 N	0.2 Nm
Accuracy	5.5 N	0.5 Nm

Movement

Pose Repeatability per ISO 9283	± 0.05 mm
---------------------------------	-----------

Axis movement	Working range	Maximum speed
Base	± 360°	± 120°/s
Shoulder	± 360°	± 120°/s
Elbow	± 360°	± 180°/s
Wrist 1	± 360°	± 180°/s
Wrist 2	± 360°	± 180°/s
Wrist 3	± 360°	± 180°/s

Typical TCP speed	1 m/s (39.4 in/s)
-------------------	-------------------

Features

IP classification	IP54
-------------------	------

ISO 14644-1 Class Cleanroom	5
-----------------------------	---

Noise	Less than 65 dB(A)
-------	--------------------

Robot mounting	Any Orientation
----------------	-----------------

I/O ports	
Digital in	2
Digital out	2
Analog in	2

Tool I/O Power Supply Voltage	12/24 V
-------------------------------	---------

Tool I/O Power Supply	2 A (Dual pin) 1 A (Single pin)
-----------------------	---------------------------------

Physical

Footprint	Ø 190 mm
-----------	----------

Materials	Aluminium, Plastic, Steel
-----------	---------------------------

Tool (end-effector) connector type	M8 M8 8-pin
------------------------------------	---------------

Cable length robot arm	6 m (236 in)
------------------------	--------------

Weight including cable	33.1 kg (73 lbs)
------------------------	------------------

Operating Temperature Range	0-50°C
-----------------------------	--------

Humidity	90%RH (non-condensing)
----------	------------------------

Control box

Features

IP classification	IP44
-------------------	------

ISO 14644-1 Class Cleanroom	6
-----------------------------	---

Operating Temperature Range	0-50°C
-----------------------------	--------

I/O ports	
Digital in	16
Digital out	16
Analog in	2
Analog out	2
Quadrature Digital Inputs	4

I/O power supply	24V 2A
------------------	--------

Communication	500 Hz Control frequency Modbus TCP PROFINET Ethernet/IP USB 2.0, USB 3.0
---------------	---

Power source	100-240VAC, 47-440Hz
--------------	----------------------

Humidity	90%RH (non-condensing)
----------	------------------------

Physical

Control box size (WxHxD)	475 mm x 423 mm x 268 mm (18.7 in x 16.7 in x 10.6 in)
--------------------------	---

Weight	12 kg (26.5 lbs)
--------	------------------

Materials	Powder Coated Steel
-----------	---------------------

Teach pendant

Features

IP classification	IP54
-------------------	------

Humidity	90%RH (non-condensing)
----------	------------------------

Display resolution	1280 x 800 pixels
--------------------	-------------------

Physical

Materials	Plastic, PP
-----------	-------------

Weight including 1m of TP cable	1.6 kg (3.5 lbs)
---------------------------------	------------------

Cable length	4.5 m (177.17 in)
--------------	-------------------